



## SCM50ASL PRO : 3 - w a y   a c t i v e

### Features

- 25mm soft dome tweeter.
- Full "SL" spec 9"/234mm bass driver.
- ATC 75mm "Super Dome" mid driver.
- On board ATC grounded plane 350W Tri-amplifier.
- LF contour control.
- Clip indication.
- 6 year warranty.

### Specifications

**Drivers :** HF 25mm, Mid 75mm, LF 234mm    **Amplitude Linearity ( $\pm 2$ dB) :** 70Hz-17kHz    **Cut-off Frequencies (-6dB, free-standing) :** 38Hz, 22kHz  
**Horizontal Dispersion :**  $\pm 80^\circ$ , Coherent    **Vertical Dispersion :**  $\pm 10^\circ$ , Coherent    **Max. Continuous SPL (1 metre) :** 112dB    **Crossover Frequencies :** 380Hz, 3.5kHz  
**Input Connectors :** Male XLR    **Input Sensitivity :** 1V    **Input Sensitivity Trim :**  $\pm 6$ dB    **Input Impedance :** Balanced > 10k $\Omega$   
**Amplifier Output :** Bass 200W, Mid 100W, High 50W    **Filters :** Even Order Critically Damped  
**Overload Protection :** Active FET momentary gain reduction plus thermal tweeter protection    **Front Panel Indicators :** Power On indicator, Gain Reduction warning  
**LF EQ :** +6dB @ 40Hz    **Dimensions (HxWxD) :** 716 x 351 x 400mm (28.2" x 13.8" x 15.8") Depth with amplifier at rear adds 3"    **Weight :** 49kg / 107.8lbs

Passive versions available. ATC reserves the right to vary products and specifications without prior notice.

