



Stream III

The previous versions of the award-winning Stream proved to be a huge success, providing an unbeatable combination of outstanding sound quality, excellent build, styling and ergonomics. The new Stream III takes this as a starting point and then completely re-defines what is achievable, with even better performance, stunning good looks, and an incredible array of useful new features.

The Stream III CD player features an all-new slot loading transport which is controlled by Leema's own custom firmware providing secure and reliable disc handling with the best retrieval of the digital information stored on the disc, with less jitter and digital error than could be achieved with off-the-shelf drives and software.

The new Leema Quad DAC is a further refinement of Leema's own highly successful MD² Multi-DAC giving a shorter signal path and even better performance.

A new feature for the Stream III is the addition of four digital inputs. These allow the connection of external digital components so that the award-winning performance for which Leema is renowned can now be extended to achieve stunning results from a whole range of digital devices such as Sky TV, the Sonos music server, and the Sony PS3.



Other products in Spectrum Series



Pulse III

Stream III



The new Stream III features a USB digital output which enables bit-perfect digital archiving.

Leema's new Navimech system provides delightfully simple and intuitive control. The elegantly svelte fascia is machined from solid aluminium to the exacting standards of Leema's state of the art metalworker who, when not machining critical mechanical components for a leading formula 1 team, is precision machining front panels and other mechanical components for Leema.

The Stream III is as beautifully made as it performs.

Technical Details

Drive	Audio optimised slot-loading assembly, Leema firmware
Digital to analogue conversion	4 x 24 bit / 192 kHz converters with low jitter receiver 1 x USB (bi-directional)
USB	16 bit / 48 kHz Burr-Brown codec, Tape out, Headphones
Analogue output level 0 dBFS (0 dB Full Scale)	Unbalanced 2.3 V RMS
Digital inputs	1 x Coax (SPDIF) 2 x Optical (SPDIF) 1 x USB (bi-directional)

Digital outputs	SPDIF RCA phono coaxial USB
Frequency response	20 Hz – 20 kHz +0.0 / -0.3 dB
Signal to noise ratio	-105 dB (A weighted)
Distortion @ 20 Hz	0.005%
Distortion @ 1 kHz	0.001%
Distortion @ 20 kHz	0.001%
M distortion 19 kHz + 20 kHz	0.001%
Linearity @ -100 dB	+/- 0.5 dB
Crosstalk @ 1 kHz	-118 dB
Crosstalk @ 10 kHz	-100 dB
Jitter	< 50 pS @ 1 kHz
Jitter total correlated	< 150 pS
Resolution	-100 dB +/- 0.2 dB
Power Supply	Six fully regulated power rails
Standby power consumption	< 0.5 W
Dimensions (W x H x D)	435 mm x 90 mm x 330 mm
Weight	9 kg

Please visit www.leema-acoustics.com to find your nearest dealer

Leema Acoustics: Award winning hi-fi



- Visit: www.leema-acoustics.com
- Phone: +44 (0)1938 811900
- Email: info@leema-acoustics.com