5 Disc CD Carousel Player



If you want the playback flexibility of a carousel changer, the playback quality of a Marantz single-disc player, and all the features that make a unit extraordinarily easy to integrate into a custom-installed system, look no further. The CC4003 answers all your needs.

Behind the CC4003's new sculptured front panel lies a 5-disc CD carousel mechanism and a host of features that make this player ideal for long-term use as a single player in a home system or part of a "whole house" system where multiple zones reproduce individually selected playlists. Indeed, the CC4003 – either alone or in multiples – is perfectly suited for these roles.

Beginning with the front panel, you'll notice immediately that the CC4003 has the same curved look that distinguishes all current Marantz products. Elegant and simple, the CC4003 augments any décor while the metal + resin composite adds strength.

The CC4003 adds WMA file playback to its predecessor's MP3 capability. So your CD-Rs and CD-RWs will play without incident. Programming capability is extended to 50 tracks for additional flexibility. And fixed-speed forward and reverse scan makes it easier to find your favorite track.

Whatever CD you choose to play, the CC4003 employs a high performance Cirrus Logic stereo D/A converter. The same converter used in some Super Audio CD players, the CS4392 produces a rich, lifelike soundfield that's far more convincing than the anemic reproduction from so-called competitive units.

Even though the CC4003 is a "carousel" changer, you can access any disc by pushing buttons on the front panel or remote controller. For even more convenience, you can replace up to three discs while one is playing.

A headphone jack with independent volume control means you can enjoy private listening any time without disturbing other household members or your neighbors even when you want to "rock your head".

In addition to gold-plated analog outputs, you'll find both coaxial and optical digital outputs so you can add the CC4003 to any system.

And integration into any system is easy, too. First, there's a bi-directional RS-232C connector so you can use a touch-screen system controller if you're so inclined. And there are RC-5 input and output jacks and an IR flasher input, in addition to a detachable AC cord. All in all, the CC4003 is ideally suited for the small spaces common to custom installations.

Thinking of using more than one CC4003 in the same system? No problems there as you can set each one (up to five) to respond to a specific set of command codes so you can control each one individually. As for mounting a CC4003 in an equipment rack, simply choose the available RMK4003CC rack-mount kit.

So get ready to enjoy the convenience of a multi-disc player – or several of them – and the sound quality of a Marantz. After all, that IS why you're looking at Marantz, isn't it?



5 Disc CD Carousel Player

Disc Capacity 5 Playback Formats CD-DA, MP3(32-320 kbps, 32/44.1/48 kHz), WMA (48-192 kbps, 32/44.1/48 kHz) Playback Formats CD-DA, MP3(32-320 kbps, 32/44.1/48 kHz), WMA (48-192 kbps, 32/44.1/48 kHz) Playback Formats CD-DA, MP3(32-320 kbps, 32/44.1/48 kHz), WMA (48-192 kbps, 32/44.1/48 kHz) Playback Formats CD-DA, MP3(32-320 kbps, 32/44.1/48 kHz), WMA (48-192 kbps, 32/44.1/48 kHz) Playback Formats CD-DA, MP3(32-320 kbps, 32/44.1/48 kHz) Playback Formats Playba	FEATURES	
Playback Formats CD-DA, MP3(32-320 kbps, 32/44.1/48 kHz), WMA (48-192 kbps, 32/44.1/48 kHz) Power Transformer EI		<u>,</u>
Power Transformer		*
Display Off CD Text Andom/Repeat Play Recording Edit Mode AMS (Auto Music Scan) Mode Peak Search Disc Changeable In Play Pitch Control Britch Control Contro		
CD Text Random/Repeat Play	- 0	
Random/Repeat Play Recording Edit Mode AMS (Auto Music Scan) Mode Peak Search Disc Changeable In Play J Discs Pitch Control Headphone level Control Headphone Out Analog L&R Out Digital Optical Out Digital Optical Out Digital Oots All Digital Out There External Control Bi-directional RS-232C D-Bus Remote (RC-5) In/Out SPECIFICATIONS AUDIO SECTION Format Sampling Frequency Af4.1 kHz Dynamic Range Frequency Response 100dB Frequency Response 2Hz - 20kHz THD 3, Natio 110dB GENERAL Color Black Front Panel Aluminum/reinforced resin Remote Control Power Requirement Power Consumption 18W (Standby: 0.6W) Dimensions W x H x D (Inches) 17 3/8 x 4 5/8 x 16		•
Recording Edit Mode		
AMS (Auto Music Scan) Mode Peak Search Disc Changeable In Play Pitch Control Headphone level Control IN/OUTPUTS AUDIO Headphone Out Analog L&R Out Digital Optical Out Digital Optical Out Digital Coaxial Out There External Control Bi-directional RS-232C D-Bus Remote (RC-5) In/Out D-Bus Rem		• / •
Peak Search - Disc Changeable In Play 3 Discs Pitch Control - Headphone level Control - IN/OUTPUTS AUDIO Headphone Out - Headphone Out 1 pair (Gold Plated) Digital Optical Out 1 Digital Coaxial Out 1 (Gold Plated) OTHER External Control Bi-directional RS-232C D-Bus Remote (RC-5) In/Out 1/1 SPECIFICATIONS AUDIO SECTION Section Format 16-Bit Linear PCM Sampling Frequency 44.1 kHz Dynamic Range 100dB Frequency Response 2Hz - 20kHz THD 0.002% S/N Ratio 110dB GENERAL Color Color Black Front Panel Aluminum/reinforced resin Remote Control - Power Consumption 18W (Standby: 0.6W) Dimensions W x H x D (Inches) 17 3/8 x 4 5/8 x 16 <td></td> <td></td>		
Disc Changeable In Play 3 Discs Pitch Control Headphone level Control Headphone Out Analog L&R Out Digital Optical Out Digital Optical Out There External Control Bi-directional RS-232C D-Bus Remote (RC-5) In/Out SPECIFICATIONS AUDIO SECTION Format Sampling Frequency Dynamic Range Frequency Response Frequency Response 100dB Frequency Response 2Hz - 20kHz THD 0 0.002% SN Ratio 110dB GENERAL Color Black Front Panel Remote Control Black Front Panel Remote Control Power Requirement Power Consumption 18W (Standby: 0.6W) Dimensions W x H x D (Inches) 17 3/8 x 4 5/8 x 16		ode .
Pitch Control - Headphone level Control - IN/OUTPUTS AUDIO Headphone Out - Analog L&R Out 1 pair (Gold Plated) Digital Optical Out 1 (Gold Plated) OTHER External Control Bi-directional RS-232C D-Bus Remote (RC-5) In/Out 1/1 SPECIFICATIONS AUDIO SECTION Somat 16-Bit Linear PCM Sampling Frequency 44.1 kHz Dynamic Range 100dB Frequency Response 2Hz - 20kHz THD 0.002% S/N Ratio 110dB GENERAL Color Black Front Panel Aluminum/reinforced resin Remote Control • Power Requirement AC 120V 60Hz Power Consumption 18W (Standby: 0.6W) Dimensions W x H x D (Inches) 17 3/8 x 4 5/8 x 16		
Headphone level Control NOUTPUTS		3 Discs
IN/OUTPUTS		
AUDIO	•	•
Headphone Out		
Analog L&R Out 1 pair (Gold Plated) Digital Optical Out 1 OTHER External Control Bi-directional RS-232C D-Bus Remote (RC-5) In/Out 1/1 SPECIFICATIONS AUDIO SECTION Format 16-Bit Linear PCM Sampling Frequency 44.1 kHz Dynamic Range 100dB Frequency Response 2Hz - 20kHz THD 0.002% S/N Ratio 110dB GENERAL Color Remote Control e Power Requirement AC 120V 60Hz Power Requirement AC 120V 60Hz Power Consumption 18W (Standby: 0.6W) Dimensions W x H x D (Inches) 17 3/8 x 4 5/8 x 16		
Digital Optical Out 1 Digital Coaxial Out 1 (Gold Plated) OTHER External Control Bi-directional RS-232C D-Bus Remote (RC-5) In/Out 1/1 SPECIFICATIONS AUDIO SECTION Format 16-Bit Linear PCM Sampling Frequency 44.1 kHz Dynamic Range 100dB Frequency Response 2Hz - 20kHz THD 0.002% S/N Ratio 110dB GENERAL Color Color Black Front Panel Aluminum/reinforced resin Remote Control • Power Requirement AC 120V 60Hz Power Consumption 18W (Standby: 0.6W) Dimensions W x H x D (Inches) 17 3/8 x 4 5/8 x 16		•
Digital Coaxial Out 1 (Gold Plated) OTHER Bi-directional RS-232C External Control Bi-directional RS-232C D-Bus Remote (RC-5) In/Out 1/1 SPECIFICATIONS AUDIO SECTION Format 16-Bit Linear PCM Sampling Frequency 44.1 kHz Dynamic Range 100dB Frequency Response 2Hz - 20kHz THD 0.002% S/N Ratio 110dB GENERAL Color Color Black Front Panel Aluminum/reinforced resin Remote Control • Power Requirement AC 120V 60Hz Power Consumption 18W (Standby: 0.6W) Dimensions W x H x D (Inches) 17 3/8 x 4 5/8 x 16	Analog L&R Out	1 pair (Gold Plated)
OTHER External Control Bi-directional RS-232C D-Bus Remote (RC-5) In/Out 1/1 SPECIFICATIONS AUDIO SECTION Format 16-Bit Linear PCM Sampling Frequency 44.1 kHz Dynamic Range 100dB Frequency Response 2Hz - 20kHz THD 0.002% S/N Ratio 110dB GENERAL Color Black Front Panel Aluminum/reinforced resin Remote Control • Power Requirement AC 120V 60Hz Power Consumption 18W (Standby:0.6W) Dimensions W x H x D (Inches) 17 3/8 x 4 5/8 x 16	Digital Optical Out	1
OTHER External Control Bi-directional RS-232C D-Bus Remote (RC-5) In/Out 1/1 SPECIFICATIONS AUDIO SECTION Format 16-Bit Linear PCM Sampling Frequency 44.1 kHz Dynamic Range 100dB Frequency Response 2Hz - 20kHz THD 0.002% S/N Ratio 110dB GENERAL Color Gont Panel Aluminum/reinforced resin Remote Control • Power Requirement AC 120V 60Hz Power Consumption 18W (Standby:0.6W) Dimensions W x H x D (Inches) 17 3/8 x 4 5/8 x 16	Digital Coaxial Out	1 (Gold Plated)
D-Bus Remote (RC-5) In/Out 1/1 SPECIFICATIONS AUDIO SECTION Format 16-Bit Linear PCM Sampling Frequency 44.1 kHz Dynamic Range 100dB Frequency Response 2Hz - 20kHz THD 0.002% S/N Ratio 110dB GENERAL Color Black Front Panel Aluminum/reinforced resin Remote Control • Power Requirement AC 120V 60Hz Power Consumption 18W (Standby: 0.6W) Dimensions W x H x D (Inches) 17 3/8 x 4 5/8 x 16	OTHER	,
SPECIFICATIONS AUDIO SECTION Format 16-Bit Linear PCM Sampling Frequency 44.1 kHz Dynamic Range 100dB Frequency Response 2Hz - 20kHz THD 0.002% S/N Ratio 110dB GENERAL Color Black Front Panel Remote Control • Power Requirement AC 120V 60Hz Power Consumption 18W (Standby: 0.6W) Dimensions W x H x D (Inches) 17 3/8 x 4 5/8 x 16	External Control	Bi-directional RS-232C
AUDIO SECTION Format 16-Bit Linear PCM Sampling Frequency 44.1 kHz Dynamic Range 100dB Frequency Response 2Hz - 20kHz THD 0.002% S/N Ratio 110dB GENERAL Color Gonote Control Aluminum/reinforced resin Remote Control • Power Requirement AC 120V 60Hz Power Consumption 18W (Standby:0.6W) Dimensions W x H x D (Inches) 17 3/8 x 4 5/8 x 16	D-Bus Remote (RC-5) In/C	Out 1/1
Format 16-Bit Linear PCM Sampling Frequency 44.1 kHz Dynamic Range 100dB Frequency Response 2Hz - 20kHz THD 0.002% S/N Ratio 110dB GENERAL Color Black Front Panel Aluminum/reinforced resin Remote Control • Power Requirement AC 120V 60Hz Power Consumption 18W (Standby: 0.6W) Dimensions W x H x D (Inches) 17 3/8 x 4 5/8 x 16	SPECIFICATIONS	
Sampling Frequency 44.1 kHz Dynamic Range 100dB Frequency Response 2Hz - 20kHz THD 0.002% S/N Ratio 110dB GENERAL Color Black Front Panel Aluminum/reinforced resin Remote Control • Power Requirement AC 120V 60Hz Power Consumption 18W (Standby: 0.6W) Dimensions W x H x D (Inches) 17 3/8 x 4 5/8 x 16	AUDIO SECTION	
Dynamic Range 100dB Frequency Response 2Hz - 20kHz THD 0.002% S/N Ratio 110dB GENERAL Color Black Front Panel Aluminum/reinforced resin Remote Control ● Power Requirement AC 120V 60Hz Power Consumption 18W (Standby: 0.6W) Dimensions W x H x D (Inches) 17 3/8 x 4 5/8 x 16	Format	16-Bit Linear PCM
Frequency Response 2Hz - 20kHz THD 0.002% S/N Ratio 110dB GENERAL Color Black Front Panel Aluminum/reinforced resin Remote Control • Power Requirement AC 120V 60Hz Power Consumption 18W (Standby:0.6W) Dimensions W x H x D (Inches) 17 3/8 x 4 5/8 x 16	Sampling Frequency	44.1 kHz
THD 0.002% S/N Ratio 110dB GENERAL Black Front Panel Aluminum/reinforced resin Remote Control • Power Requirement AC 120V 60Hz Power Consumption 18W (Standby:0.6W) Dimensions W x H x D (Inches) 17 3/8 x 4 5/8 x 16	Dynamic Range	100dB
S/N Ratio 110dB GENERAL	Frequency Response	2Hz - 20kHz
S/N Ratio 110dB GENERAL Black Color Black Front Panel Aluminum/reinforced resin Remote Control • Power Requirement AC 120V 60Hz Power Consumption 18W (Standby:0.6W) Dimensions W x H x D (Inches) 17 3/8 x 4 5/8 x 16	THD	0.002%
GENERAL Color Black Front Panel Aluminum/reinforced resin Remote Control • Power Requirement AC 120V 60Hz Power Consumption 18W (Standby: 0.6W) Dimensions W x H x D (Inches) 17 3/8 x 4 5/8 x 16	S/N Ratio	
Front Panel Aluminum/reinforced resin Remote Control Power Requirement AC 120V 60Hz Power Consumption 18W (Standby:0.6W) Dimensions W x H x D (Inches) 17 3/8 x 4 5/8 x 16	GENERAL	
Remote Control Power Requirement AC 120V 60Hz	Color	Black
Remote Control • Power Requirement AC 120V 60Hz Power Consumption 18W (Standby:0.6W) Dimensions W x H x D (Inches) 17 3/8 x 4 5/8 x 16	Front Panel	Aluminum/reinforced resin
Power Consumption 18W (Standby:0.6W) Dimensions W x H x D (Inches) 17 3/8 x 4 5/8 x 16	Remote Control	,
Power Consumption 18W (Standby:0.6W) Dimensions W x H x D (Inches) 17 3/8 x 4 5/8 x 16	Power Requirement	AC 120V 60Hz
Dimensions W x H x D (Inches) 17 3/8 x 4 5/8 x 16		
weight (ibs) 15.4	Weight (lbs)	15.4







*All specifications, dimensions and weights are subject to change without notice.

D&M Holdings, Marantz, Marantz America, Inc. or any of its subsidiaries will not assume any liability for errors in this spec sheet which may result in consequential errors being made by retail dealers, designers, custom installers, cabinet makers or end users, etc based upon information contained within this document.