

Centre speaker: CC 51



The new 2-way centre channel speaker CC 51 of the new 50 series provides excellent intelligibility and wide sound dispersion. It offers a spectacular sound stage for home cinema performances. The new CC 51 can be used with standard hi-fi racks due to its compact dimensions. This centre loudspeaker is magnetically shielded and therefore may be used near TV sets.

Technical features

- 2 x 140 mm woofer, magnetically shielded, for balanced sound and high efficiency with cellulose diaphragm and concave-shaped capton bobbin for good power handling
- 1 x 25 mm tweeter with neodymium magnet system and star-shaped cooling attachment on the terminal
- gold-plated mono binding posts with transparent screw-type terminal
- the bass port's double flare design minimises air noise and friction losses
- overload-protection provides trouble free operation: this loudspeaker is recommended for use with 20-100W/ch powerful amplifiers
- elegant design: all driver baskets and mounting plates of the 50 series are in the new colour *titan metallic*, specially designed for ELAC
- magnetically shielded



Finishes: graphite maple, cherry, silver

Specifications	ELAC CC 51	Crossover Frequency	2400 Hz
Dimensions H x W x D	170 x 435 x 265/250 mm	Nominal / Peak Power Handling	70 W / 110 W
Weight	approx. 7 kg	Frequency Range	48-23000 Hz
Type	2 way, bass reflex	Sensitivity	90 dB/2.8V/m
Woofer	2 x 145 mm cone	Nominal Impedance	6 ohms
Tweeter	1 x 25 mm dome	Minimum Impedance	4.6 ohms at 230 Hz
Rec. Amplifier Power at Nominal Impedance	20 – 150 W/channel		

FINEST GERMAN ENGINEERING
ELAC

CC 51

Product Information