

CINEMA 24 CM: Elegance and flexibility

This new 2 ½ way universal loudspeaker in aluminium design can be used as a main and centre speaker. Thanks to its compact dimensions, it can be used for all TV racks. Special wall brackets can be adjusted to suit vertical or horizontal mounting, and allow even larger cable diameters.

The same applies to the ELAC logo – it can be adjusted vertically or horizontally. CINEMA 24 CM can be used with an optional high-quality glass base.

In combination with a subwoofer, this slender speaker is part of a highly efficient system suitable for high levels or larger rooms and for high-quality stereo reproduction, home cinema, hi-fi and surround sound!



Technical features

- 25mm silk dome tweeter with Ferro fluid cooling driven by a strong neodymium magnet system to provide good sound and reliability
- 80mm woofer with long-life rubber surround and cellulose cone for neutral performance; high efficiency due to fourfold use
- will work well with less powerful amplifiers due to amplifier-friendly impedance of 6 Ohms
- shielded magnet systems for trouble free use near TV sets
- high-pass filter integrated on the crossover network protect the bass drivers from mechanical overload
- new terminal is easy to access and allows larger cable diameters (4 mm²)
- reversible fuse guarantees trouble free use

Finishes: silver

Set-up options



Specifications	ELAC CINEMA 24 CM		
Dimensions H x W x D	88 x 610 x 102 mm	Crossover Frequency	900/3800 Hz
Weight	approx. 4.5 kg	Nominal/Peak Power Handling	80 W/110 W
Type	2 ½-way, closed, integrated high-pass filter	Frequency range	80-21.000 Hz
Midrange tweeter	4 x 80 mm cone	Sensitivity	90 dB/2,8V/m
Tweeter	1 x 25 mm dome	Nominal impedance	6 Ohms
Recom. Amplifier Power at Nom. Impedance	20 – 150 W / channel	Minimum impedance	4.8 Ohms at 360 Hz

