

## CINEMA 2 SAT: Small in size but large in effect



This small satellite is a universally applicable surround component that can be used as an effect loudspeaker, as well as a centre speaker or main speaker (in combination with a subwoofer.)

It performs well-balanced and dynamic sound. Noble aluminium design and hairline finish ensure optical delight for your pleasure! The wall brackets included with the set allow inobtrusive wall mounting; slender stands are available as accessory.

### Technical Features and Benefits

- high performance ringdome mylar tweeter with neodymium magnet system as well as waveguide and phaser for an optimum dispersion characteristic.
- 2 concave-shaped



- midrange woofers for high efficiency
- amplifier-friendly impedance of 6 Ohms
- high-pass filters integrated on the crossover network protect the drivers from mechanical strain
- well-balanced linearity
- input terminal providing bigger and inclined sockets for better access, suitable for large cable diameters
- shielded magnet systems

*Finishes: silver brushed aluminium, black brushed aluminium*



### Technische Daten CINEMA 2 SAT

Dimensions H x W x D	132 x 88 x 102 mm	Crossover Frequency	3800 Hz
Gross Volume	0,85 l	Nominal Peak/ Power Handling	45 W / 65 W
Type	2 -way, closed, integr. high-pass filter	Frequency Range	90...21.000 Hz
Midrange woofers	2 x cone 80 mm	Sensitivity	85 dB/2.83V/m
Tweeter	1 x dome 19 mm	Nominal Impedance	6 Ohms
Suitable for amplifiers from ...	4-8 Ohms	Minimum Impedance	4,8 Ohms at 450 Hz
Rec. Amplifier Power at Nom. Impedance	20-150 W/Channel		

featuring CINEMA 2 SAT



**ELAC**