CINEMA XL CENTER: Vivid elegance in the limelight



This new centrespeaker ideally completes our mini home theatre system CINEMA 2 ESP!

CINEMA XL CENTER is a powerful speaker that perfectly matches with CINEMA PIPE or satellite CINEMA 2 SAT 6 Ohm. The tiny speaker meets the highest demands required in any surround

CINEMA XL CENTER performs well-balanced and dynamic sound. Noble aluminium design and hairline finish ensures optical delight for your pleasure!

Due to its flat shape, CINEMA XL CENTER can be mounted very easily.







Technical Features and Benefits

- 25mm silk dome tweeter driven by a neodymium magnet system with ferrofluid cooling to provide good sound and reliability
- 2 concave-shaped midrange woofers for high efficiency
- 80 mm high-power woofer with long-life rubber surround and cellulose cone damped on the back, for neutral performance
- amplifier-friendly impedance of 6 Ohms
- well-balanced linearity providing good intelligibility
- trouble free use is guaranteed by overload-protected
- rugged extruded aluminium cabinet with hairline finish
- input terminal providing bigger and inclined sockets for better access, suitable for large cable diameters (4 gmm)
- new type of wall brackets for discreet mounting
- shielded magnet systems for trouble free use near TV sets

Finishes: silver brushed aluminium



Specifications CINFMA XI CENTER

Specifications Citation AL CLIVILIX				
Dimensions H x W	x D 88 x 29	0 x 102 mm	Crossover Frequency	3800 Hz
Gross Volume		1.9 I	Nominal/Peak Power Handling	60/80 W
Weight		2.1 kg	Frequency Range	8521,000 Hz
Туре	2 -way, closed, integr. hi	gh-pass filter	Sensitivity	87 dB/2.83V/m
Midrange woofers	2 x	80mm cone	Nominal Impedance	6 Ohms
Tweeter	1 x 2	25mm dome	Minimum Impedance	4.8 Ohms at 450 Hz
Suitable for amplifie	rs fromto	4-8 Ohms	Recom. Amplifier Power at	
			Nom. Impedance	20-150 W/channel