

## NEU! / NEW! - Linie 50.2 / 50.2 series - BS 53.2



### Merkmale / Features:

- Chassis in moderner schwarz / silber Optik
- Lautsprechergitter im Lieferumfang
- Schallwand in Schwarz Lack Seidenmatt, umlaufend 4er Radius
- Zarge in Dekor, ebenfalls mit 4er Radius (bis auf Rückwand)
- Neu entwickelter Gewebe-Hochtöner mit luftig-brillantem Klang
- Optimierte Tieftöner mit langzeitstabiler Gummisicke und knackig-kräftigem Bass
- Drivers in modern black / silver impression
- Speaker grille within scope of delivery
- Front baffle in Black Matt lacquer, circumferential 4 mm radius
- Cabinet also with 4 mm radius (not rear baffle)
- Newly developed silk dome tweeter with light and brilliant sound
- Improved woofer with long term rugged rubber surround and powerful tight bass

**Farbausführungen / Colors:** Esche Schwarz, Kirsche Dunkel / Black Ash, Dark Cherry Finish

### Technische Daten / Specifications:

Dimensions:		[mm]
Height	285	
Width	170	
Depth	220 / 235	(w/o / w Grille)
Weight	ca. 5.5	[kg]
Type	2-	Way, Bassreflex
Woofer	1x 145	[mm] Ø Cone
Bassreflex Tube	1x 45	[mm] Ø
Mid Range	-	[mm] Ø Cone
Tweeter	1x 25	[mm] Ø Dome
Crossover Frequency	2200	[Hz]
Nominal Power Handling	50	[W]
Peak Power Handling	70	[W]
Frequency Range (IEC 268-5)	46...25 000	[Hz]
Sensitivity	87	[dB / 2.83V / m]
Suitable for Amplifiers from ... to	4 - 8	[Ω]
Nominal Impedance	4	[Ω]
Minimum Impedance	3.7 / 210	[Ω / Hz]
Recommended Amplifier Power at Nominal Impedance	20 -120	[W / Channel]

Product Information BS 53.2

FINEST GERMAN ENGINEERING  
ELAC