

## NEU! / NEW! - Linie 50.2 / 50.2 series - FS 58.2



### Merkmale / Features:

- Chassis in moderner schwarz / silber Optik
- Lautsprechergitter im Lieferumfang
- Schallwand und Bodenplatte in Schwarz Lack Seidenmatt, umlaufend 4er Radius
- Zarge in Dekor, ebenfalls mit 4er Radius (bis auf Rückwand)
- Neu entwickelter Gewebe-Hochtöner mit luftig-brillantem Klang
- Optimierte Tieftöner mit langzeitstabiler Gummisicke und knackig-kräftigem Bass
- Spikes mit Spike Scheiben im Lieferumfang
- Drivers in modern black / silver impression
- Speaker grille within scope of delivery
- Front baffle and bottom plate in black matt lacquer, circumferential 4 mm radius
- Cabinet also with 4 mm radius (not rear baffle)
- Newly developed silk dome tweeter with light and brilliant sound
- Improved woofer with long term rugged rubber surround and powerful tight bass
- Spikes and Spike Washers within scope of delivery

**Farbausführungen / Colors:** Esche Schwarz, Kirsche Dunkel / Black Ash, Dark Cherry Finish

### Technische Daten / Specifications:

Dimensions:		[mm]
Height	1030 / 1055 / 1070	(w/o / w/ Bottomplate./ Spikes)
Width	200 / 250	(w/o / w/ Bottomplate)
Depth	285 / 300 / 335	(w/o / w/ Grille / Bottomplate.)
Weight	ca. 20	[kg] (w/ Bottomplate)
Type	3-	Way, Bassreflex
Woofer	2x 175	[mm] Ø Cone
Bassreflex Tube	2x 58	[mm] Ø
Mid Range	1x 145	[mm] Ø Cone
Tweeter	1x 25	[mm] Ø Dome
Crossover Frequency	600 / 2400	[Hz]
Nominal Power Handling	100	[W]
Peak Power Handling	140	[W]
Frequency Range (IEC 268-5)	38...25 000	[Hz]
Sensitivity	90	[dB / 2.83V / m]
Suitable for Amplifiers from ... to	4 - 8	[Ω]
Nominal Impedance	4	[Ω]
Minimum Impedance	3.2 / 130	[Ω / Hz]
Recommended Amplifier Power at Nominal Impedance	20 - 180	[W / Channel]

Product Information FS 58.2

FINEST GERMAN ENGINEERING  
**ELAC**