

## NEU! / NEW! - Linie 60.2 / 60.2 series - FS 67.2



### Merkmale / Features:

- Moderne, hochwertige Klangabstimmung
- Keine sichtbaren Schrauben auf der Front
- Durch neue Faceplate Konstruktion nur Hochtongitter und Tieftonmembranen sichtbar
- Magnetische Befestigung des Bespannrahmens (weder Stifte, noch Buchsen sichtbar!)
- Faceplate: Hochglanz-Schwarz Dekor.
- Korpus: Esche Schwarz Dekor, bzw. Walnuss Dunkel Dekor
- Bodenplatte: Schwarz Lack Seidenmatt
- Zum Lieferumfang gehören: Bass Reflex Stopfen, Spikes und Spike Scheiben
- *Modern, high-grade sound*
- *No visible screws at the front*
- *Only tweeter grille and woofer diaphragms visible because of new faceplate construction*
- *Cloth grille fixed by magnets (neither pins, nor catchers visible!)*
- *Faceplate in Black High Gloss Finish*
- *Cabinet either in Black Ash or in Dark Walnut Finish*
- *Bottom plate in Black Matt Finish*
- *Scope of delivery contains: bass reflex plugs, spikes and spike washers*

**Farbausführungen / Colors:** Esche Schwarz, Walnuss Dunkel / *Black Ash, Dark Walnut*

### Technische Daten / Specifications:

Dimensions:		[mm]
Height	900 / 925 / 950	(w/o / w/ Bottomplate./ Spikes)
Width	170 / 220	(w/o / w/ Bottomplate)
Depth	250 / 265 / 300	(w/o / w/ Grille / Bottomplate.)
Weight	14.5	[kg] (w/ Bottomplate)
Type	2 ½-	Way, Bassreflex
Woofer	2x 140 AS	[mm] Ø Cone
Mid Range	-	[mm] Ø Cone
Tweeter	1x 25	[mm] Ø Dome
Crossover Frequency	500 / 2200	[Hz]
Nominal Power Handling	80	[W]
Peak Power Handling	120	[W]
Frequency Range (IEC 268-5)	38...25 000	[Hz]
Sensitivity	88	[dB / 2.83V / m]
Suitable for Amplifiers from ... to	4 - 8	[Ω]
Nominal Impedance	6	[Ω]
Minimum Impedance	5.2 / 220	[Ω / Hz]
Recommended Amplifier Power at Nominal Impedance	20 – 150	[W / Channel]

Product Information FS 67.2

FINEST GERMAN ENGINEERING  
**ELAC**