



Double bass centre speaker, mini satellites, powerful subwoofer = great soundstage in miniature design



Mini sets providing huge soundstages are en vogue. Impossible? Not at all. The new Starlet 5.1 combines high-tech musical performance and ambience-friendly design!

The **Starlet CM** offers extraordinary clarity and high efficiency. All drivers are magnetically shielded. It is suitable for horizontal or vertical mounting. Starlet CM provides an outstanding listening zone (even when positioned horizontally). Cross-over network with integrated high pass filter protects drivers against mechanical strain.

Mini satellite **Starlet** with integrated high pass filter and powerful ringdome tweeter with waveguide for improved horizontal dispersion. The drivers are magnetically shielded.



This loudspeaker plays up to 21000Hz. High-power voice coil with ferrofluid cooling and metallized aluminium diaphragm for minimized resonances. 80mm woofer with rubber surround, metallized aluminium diaphragm and magnetically shielded magnet system. The inclined binding posts of the terminal are easy to access.

Deep bass sound is provided by the subwoofer **SUB 111.2 ESP**. ESP® is a frequency and power dependent electronic stabilisation programme for protection against overdrive. In comparison to conventional active subwoofers, it is now practically impossible to overdrive ELAC ESP® subwoofers.

The Starlet 5.1 is a powerful mini ensemble for the best value for money! The satellites are suitable for all stereo applications and can be used as effect speakers in every home cinema set.

Wall brackets for unobtrusive mounting and slender loudspeaker stands are available as accessory.

Finishes: black high gloss



Technical specifications:

	Starlet (4x)	Starlet CM (1x)	SUB 111.2 ESP (1x)
	surround loudspeaker	centre loudspeaker	active subwoofer
Dimensions H x B x T	117 x 90 x 100 mm	90 x 215 x 100 mm	400 x 257 x 380/396 mm
Type	2-way, closed, integr. high pass filter	2-way, closed, integr. high pass filter	1-way, bass reflex, active, 3 input channels
Tweeter	1 x 19 mm Ringdome, magn. shielded	1 x 19 mm Ringdome, magn. shielded	-
Woofer	1 x 80 mm cone, magn. shielded	2 x 80 mm cone, magn. shielded	1 x 200mm AS cone
Nominal / Peak Power Handling	40/60 W	55/75	-
Max Amplifier Power	-	-	80 W (sine), 100 W (pulse)
Frequency Range	100 ... 21000 Hz	95...21.000 Hz	35 ... 240 Hz
Finishes	Black highgloss	black, highgloss	black